



## Telescopic Boom Crane

伸缩臂型船用吊车

Specifications 技术规格	
Drive 动力驱动	Electric Hydraulic Drive 电力液压驱动
Configuration 结构形式	Telescopic boom marine crane 伸缩臂型全回转船用吊车
Type 工作类型	Shipboard /Offshore Marine Crane 内海型/开放海域船用吊车
Tilting Moment 倾覆力矩	30~800 TM, 30~800 吨米
Max. Outreach 工作范围	2~25 meters 2~25 米
Wire Speed 绳速	Complying With ISO/Classification Society Requirement/customer's requirement 依照 ISO/船级社规范/客户需求
Safety Working Load 安全工作载荷	1~ 25 Tones 1-25 吨
Hook Travel 吊钩工作行程	20~450 Meters 20~450 米
Luffing Time 臂架俯仰速度	40~120 sec 40~120 秒
Telescopic Time 臂架伸缩速度	30~120sec 30~120 秒
Emergency Release 紧急释放	Hoisting, Luffing cylinders, telescopic cylinders, slewing Emergency Release 卷扬、举升油缸、伸缩油缸、回转驱动紧急释放
Control 控制	Local Control Console/ Joystick cabin Control 机旁控制/驾驶室联动台控制
Certificate 证书	Manufacture certificate/class certificate/certificate of original. 工厂证书/船检证书/原产地证
Power Pack 动力	Hydraulic /Electric-Hydraulic/Diesel Engine 液压/电动-液压/柴油机, 内置/外置